


MSDS	Material Safety Data Sheet	24 Hour Emergency Telephone: 908-859-2151 CHEMTREC: 1-800-424-9300
		National Response in Canada CANUTEC: 613-996-6666
		Outside U.S. and Canada Chemtrec: 703-527-3887
		NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.
From: Mallinckrodt Baker, Inc. 222 Red School Lane Phillipsburg, NJ 08865		
All non-emergency questions should be directed to Customer Service (1-800-582-2637) for assistance.		

DI IODOMETHANE

1. Product Identification

Synonyms: Methane, diiodo-; methylene iodide
CAS No.: 75-11-6
Molecular Weight: 267.84
Chemical Formula: CH₂I₂
Product Codes:
J.T. Baker: J219
Mallinckrodt: 1877

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Diiodomethane	75-11-6	90 - 100%	Yes

3. Hazards Identification

Emergency Overview

DANGER! CORROSIVE. CAUSES BURNS TO ANY AREA OF CONTACT. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 2 - Moderate
Flammability Rating: 0 - None
Reactivity Rating: 1 - Slight
Contact Rating: 3 - Severe (Corrosive)
Lab Protective Equip: GOGGLES; LAB COAT; PROPER GLOVES
Storage Color Code: White (Corrosive)

Potential Health Effects

Information on the human health effects from exposure to this substance is limited.

Inhalation:

Corrosive. Extremely destructive to tissues of the mucous membranes and upper respiratory tract. Symptoms may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea and vomiting. Inhalation may be fatal as a result of spasm inflammation and edema of the larynx and bronchi, chemical pneumonitis and pulmonary edema.

Ingestion:

Corrosive. Swallowing can cause severe burns of the mouth, throat, and stomach. Can cause sore throat, vomiting, diarrhea.

Skin Contact:

Corrosive. Symptoms of redness, pain, and severe burn can occur. May be absorbed through the skin with possible systemic effects.

Eye Contact:

Corrosive. Contact can cause blurred vision, redness, pain and severe tissue burns.

Chronic Exposure:

No information found.

Aggravation of Pre-existing Conditions:
No information found.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion:

If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact:

Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, immediately. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Flash point: > 113C (> 235F)

Fire may produce toxic fumes.

Explosion:

Not considered to be an explosion hazard. Sealed containers may rupture when heated.

Fire Extinguishing Media:

Water spray, dry chemical, alcohol foam, or carbon dioxide.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer!

7. Handling and Storage

Keep in a tightly closed light-resistant container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

-ACGIH (TWA) for Iodides:

0.01 ppm for inhalable fraction and vapor.

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

For conditions of use where exposure to the substance is apparent, consult an industrial hygienist. For emergencies, or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Yellow, very heavy, highly refractive liquid.

Odor:

No information found.

Solubility:

Insoluble in water.

Specific Gravity:

3.325

pH:

No information found.

% Volatiles by volume @ 21C (70F):

No information found.

Boiling Point:

181C (358F)

Melting Point:

6C (43F)

Vapor Density (Air=1):

9.25

Vapor Pressure (mm Hg):

No information found.

Evaporation Rate (BuAc=1):

No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage. Darkens on exposure to light, air, and moisture.

Hazardous Decomposition Products:

Burning may produce toxic iodine vapors.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Potentially explosive reaction with diethyl zinc and alkenes. Violent reaction with copper-zinc alloys and ether. Forms very shock-sensitive explosive mixtures with potassium, potassium-sodium alloys and lithium. Containers may explode in heat or fire. Strong oxidizing agents, strong bases.

Conditions to Avoid:

Air, moisture, light and incompatibles. Incompatibles.

11. Toxicological Information

No LD50/LC50 information found relating to normal routes of occupational exposure.

-----\Cancer Lists\-----			
Ingredient	---NTP Carcinogen---		IARC Category
	Known	Anticipated	
Diiodomethane (75-11-6)	No	No	None

12. Ecological Information

Environmental Fate:

No information found.

Environmental Toxicity:

No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N. O. S. (DIIODOMETHANE)
Hazard Class: 8
UN/NA: UN3265
Packing Group: II
Information reported for product/size: 100ML

International (Water, I. M. O.)

Proper Shipping Name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N. O. S. (DIIODOMETHANE)
Hazard Class: 8
UN/NA: UN3265
Packing Group: II
Information reported for product/size: 100ML

International (Air, I. C. A. O.)

Proper Shipping Name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N. O. S. (DIIODOMETHANE)
Hazard Class: 8
UN/NA: UN3265
Packing Group: II
Information reported for product/size: 100