

Material Safety Data Sheet

Dyno Nobel Inc.

2650 Decker Lake Boulevard, Suite 300
Salt Lake City, Utah 84119
Phone: 801-364-4800 Fax: 801-321-6703
E-Mail: dnn.hse@am.dynonobel.com

FOR 24 HOUR EMERGENCY, CALL **CHEMTREC (USA) 800-424-9300**
CANUTEC (CANADA) 613-996-6666

MSDS # 1126**Date 01/24/05**

Supersedes
MSDS # 1126 10/20/03

SECTION I - PRODUCT IDENTIFICATION

Trade Name(s): PRIMALINE®
PRIMACORD®
PRIMASHEAR™
OPTICORD®
GEOSEIS®
LOW FLEX™
FIRELINE CORD

Product Class: Detonating Cord

Product Appearance & Odor: Flexible cord of woven textile with a protected explosive core of PETN (white crystalline powder) and covered by a white or colored plastic or textile jacket. May have a waxed finish. No odor.

DOT Hazard Shipping Description: Cord, Detonating 1.1D UN0065 II

NFPA Hazard Classification: Not Applicable (See Section IV - Special Fire Fighting Procedures)

SECTION II - HAZARDOUS INGREDIENTS

Ingredients	CAS#	%	<u>Occupational Exposure Limits</u>	
			OSHA PEL-TWA	ACGIH TLV-TWA
Pentaerythritol tetranitrate (PETN)	78-11-5	-----*	None ¹	None ²

¹ Use limit for particulates not otherwise regulated (PNOR): Total dust, 15 mg/m³; respirable fraction, 5 mg/m³.

² Use limit for particulates not otherwise classified (PNOC): Inhalable particulate, 10 mg/m³; respirable part., 3 mg/m³.

Ingredients, other than those mentioned above, as used in this product are not hazardous as defined under current Department of Labor regulations, or are present in de minimus concentrations (less than 0.1% for carcinogens, less than 1.0% for other hazardous materials).

* Core powder is 100% PETN. The approximate amount of PETN in a given grade of cord is expressed as that number of grams of PETN per linear meter of cord. Range is from 1 to 280 gram/meter. Example: PRIMALINE® 5 contains approximately 5 grams PETN per meter of cord. (1 gram/meter = 4.7 grains/foot)

SECTION III - PHYSICAL DATA

Boiling Point: Not Applicable (PETN decomposes at melting point, about 141°C)

Vapor Pressure: Not Applicable

Percent Volatile by Volume: Not Applicable

Vapor Density: (Air = 1) Not Applicable

Solubility in Water: Insoluble.

Material Safety Data Sheet

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Extinguishing Media: (See Special Fire Fighting Procedures section.)

Special Fire Fighting Procedures: Do not attempt to fight fires involving explosive materials. Evacuate all personnel to a predetermined safe, distant location. Allow fire to burn unless it can be fought remotely or with fixed extinguishing systems (sprinklers). For transportation fires involving large quantities of detonating cord, such as a trailer load, evacuate no less than 2,500 feet in all directions.

Unusual Fire and Explosion Hazards: Can explode or detonate under fire conditions. Burning or detonating material may produce toxic vapors.

SECTION V - HEALTH HAZARD DATA

Effects of Overexposure

This is a packaged product that will not result in exposure to the explosive core material under normal conditions of use.

Eyes: May cause irritation, redness and tearing.

Skin: PETN is not known as a skin irritant or sensitizer.

Ingestion: PETN is moderately toxic if ingested. See systemic effects below.

Inhalation: See systemic effects below.

Systemic or Other Effects: PETN is a known coronary vasodilator, and ingestion or inhalation may result in a lowering of blood pressure, headache or faintness, and a decreased tolerance for grain alcohol. Repeated over-exposure may result in chest pains in the absence of exposure. Systemic effects by ingestion include dermatitis.

Carcinogenicity: No constituents are listed by NTP, IARC or OSHA.

Emergency and First Aid Procedures

Eye: Irrigate with running water for at least fifteen minutes. If irritation persists, seek medical attention.

Skin: Wash with soap and water.

Ingestion: Seek medical attention.

Inhalation: Remove to fresh air. If symptoms persist, seek medical attention.

Special Considerations: None.

SECTION VI - REACTIVITY DATA

Stability: Stable under normal conditions, may explode when subjected to fire, supersonic shock or high-energy projectile impact, especially when confined or in large quantities.

Conditions to Avoid: Keep away from heat, flame, ignition sources, impact, friction, electrostatic discharge and strong shock.

Materials to Avoid (Incompatibility): Corrosives (strong acids and strong bases or alkalis).

Hazardous Decomposition Products: Nitrogen Oxides (NO_x), Carbon Monoxide (CO)

Hazardous Polymerization: Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Protect from all ignition sources. In case of fire evacuate all personnel to a safe distant area and allow to burn or fight fire remotely. Notify authorities in accordance with emergency response procedures. Only personnel trained in emergency response should respond. If explosive powder is spilled from damaged detonating cord, remove all other explosives from the spill area. Wet down and clean spilled powder using a damp sponge or rag, avoid applying friction or pressure to the explosive, and place in a (Velostat) electrically conductive bag. Contamination of this material with sand, grit or dirt will render the material more sensitive to detonation. If no fire danger is present, and product is undamaged and/or uncontaminated, repackage product in original packaging or other

Material Safety Data Sheet

clean DOT approved container. Ensure that a complete account of product has been made and is verified. Follow applicable Federal, State, and local spill reporting requirements.

Waste Disposal Method: Disposal must comply with Federal, State and local regulations. If product becomes a waste, it is potentially regulated as a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR, part 261. Review disposal requirements with a person knowledgeable with applicable environmental law (RCRA) before disposing of any explosive material.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Not required for normal handling.

Respiratory Protection: None normally required.

Protective Clothing: Work gloves and work clothing that reduce the possibility of skin abrasion and that would prevent contact with spilled explosive powder is suggested.

Eye Protection: Safety glasses or goggles are recommended.

Other Precautions Required: None.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in cool, dry, well-ventilated location. Store in compliance with Federal, State and local regulations. Only properly qualified and authorized personnel should handle and use explosives. Keep away from heat, flame, ignition sources, impact, friction, electrostatic discharge and strong shock.

Precautions to be taken during use: Use accepted safe industry practices when using explosive materials. Unintended detonation of explosives or explosive devices can cause serious injury or death. Avoid breathing the fumes or gases from detonation of explosives. Detonation in confined or unventilated areas may result in exposure to hazardous fumes or oxygen deficiency.

Other Precautions: It is recommended that users of explosive materials be familiar with the Institute of Makers of Explosives Safety Library Publications.

SECTION X - SPECIAL INFORMATION

This product contains the following substances that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

<u>Chemical Name</u>	<u>CAS Number</u>	<u>% By Weight</u>
None		

Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.