


MSDS Material Safety Data Sheet	24 Hour Emergency Telephone: 908-859-2151 CHEMTREC: 1-800-424-9300
	National Response in Canada CANUTEC: 613-996-6666
From: Mallinckrodt Baker, Inc. 222 Red School Lane Phillipsburg, NJ 08865	Outside U.S. and Canada Chemtrec: 703-527-3887
 Mallinckrodt CHEMICALS J.T. Baker	NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.
All non-emergency questions should be directed to Customer Service (1-800-582-2537) for assistance.	

ISOBUTYL ALCOHOL

1. Product Identification

Synonyms: 1-Hydroxymethylpropane; isobutanol; 2-methylpropanol; 2-methyl-1-propanol; Isopropylcarbinol
CAS No. : 78-83-1
Molecular Weight: 74.12
Chemical Formula: (CH₃)₂ CHCH₂OH
Product Codes:
J. T. Baker: 9044, 9047, 9048
Mallinckrodt: 3002

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Isobutyl Alcohol	78-83-1	100%	Yes

3. Hazards Identification

Emergency Overview

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 2 - Moderate
Flammability Rating: 2 - Moderate
Reactivity Rating: 1 - Slight
Contact Rating: 2 - Moderate (Life)
Lab Protective Equip: GOGGLES; LAB COAT; VENT HOOD; PROPER GLOVES; CLASS B EXTINGUISHER
Storage Color Code: Red (Flammable)

Potential Health Effects

Inhalation:

Causes irritation to respiratory tract. Effects from overexposure include headache, dizziness, muscle weakness, drowsiness, incoordination, confusion, and coma. High concentrations can cause central nervous system damage, pulmonary edema, and liver damage. Death may occur from respiratory failure.

Ingestion:

Ingestion may cause nausea, vomiting, and diarrhea. Large doses may cause central nervous system damage, pulmonary edema, and liver damage. Death may occur from respiratory failure.

Skin Contact:

Skin contact causes irritation, redness, and pain. May be absorbed through the skin; symptoms of absorption may be similar to those from ingestion exposure.

Eye Contact:

Vapors cause irritation, redness, and blurred vision. Splashes may cause severe irritation or eye damage.

Chronic Exposure:

Prolonged or repeated skin exposure may cause dermatitis.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person.

Skin Contact:

Remove any contaminated clothing. Wash skin with soap or mild detergent and water for at least 15 minutes. Wash clothes before reuse. Get medical attention if irritation develops or persists.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Flash point: 28C (82F) CC

Autoignition temperature: 415C (779F)

Flammable limits in air % by volume:

lcl: 1.7; ucl: 10.6

Flammable Liquid and Vapor!

Explosion:

Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Containers may explode in heat or fire.

Fire Extinguishing Media:

Dry chemical, foam or carbon dioxide. Do not use a solid stream of water, since the stream will scatter and spread the fire. Water spray may be used to keep fire exposed containers cool.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Vapors can flow along surfaces to distant ignition source and flash back.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

J. T. Baker SOLUSORB?solvent adsorbent is recommended for spills of this product.

7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL): 100 ppm (TWA)

-ACGIH Threshold Limit Value (TLV): 50 ppm (TWA)

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded, a full facepiece respirator with organic vapor cartridge may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Clear, colorless solution.

Odor:

Sweet-musty odor.

Solubility:

9.5g/100ml water @ 20C (68F).

Specific Gravity:

0.803

pH:

No information found.

% Volatiles by volume @ 21C (70F):

100

Boiling Point:

108C (226F)

Melting Point:

-108C (-162F)

Vapor Density (Air=1):

2.6

Vapor Pressure (mm Hg):

8.8 @ 20C (68F)

Evaporation Rate (BuAc=1):

0.8

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Burning may produce carbon monoxide, carbon dioxide and isobutylene.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Oxidizing agents, inorganic acids, aldehydes, isocyanates.

Conditions to Avoid:

Heat, flames, ignition sources and incompatibles.

11. Toxicological Information

Isobutyl alcohol: Oral rat LD50: 2460 mg/kg. Skin rabbit LD50: 3400 mg/kg. Irritation data: Skin rabbit 500 mg/24H moderate. Eye, open, rabbit 2mg severe; Investigated as a tumorigen and a mutagen.

-----\Cancer Lists\-----

Ingredient	---NTP Carcinogen---		IARC Category
	Known	Anticipated	
Isobutyl Alcohol (78-83-1)	No	No	None

12. Ecological Information

Environmental Fate:

When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material is expected to quickly evaporate. This material has a log octanol-water partition coefficient of less than 3.0. When released to water, this material is expected to quickly evaporate. When released into water, this material is expected to readily biodegrade. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals.

Environmental Toxicity:

This material is not expected to be toxic to aquatic life. The LC50/96-hour values for fish are over 100 mg/l.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: ISOBUTANOL

Hazard Class: 3

UN/NA: UN1212

Packing Group: III

Information reported for product/size: 20L

International (Water, I.M.O.)

Proper Shipping Name: ISOBUTANOL

Hazard Class: 3

UN/NA: UN1212

Packing Group: III

Information reported for product/size: 20L

15. Regulatory Information

-----\Chemical Inventory Status - Part 1\-----				
Ingredient	TSCA	EC	Japan	Australia
Isobutyl Alcohol (78-83-1)	Yes	Yes	Yes	Yes

-----\Chemical Inventory Status - Part 2\-----				
Ingredient	Korea	--Canada--		
		DSL	NDSL	Phil.
Isobutyl Alcohol (78-83-1)	Yes	Yes	No	Yes

-----\Federal, State & International Regulations - Part 1\-----				
Ingredient	-SARA 302-		-SARA 313-	
	RQ	TPQ	List	Chemical Catg.
Isobutyl Alcohol (78-83-1)	No	No	No	No

-----\Federal, State & International Regulations - Part 2\-----			
Ingredient	CERCLA	-RCRA-	-TSCA-
		261.33	8(d)
Isobutyl Alcohol (78-83-1)	5000	U140	No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: Yes
 SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No
 Reactivity: No (Pure / Liquid)

Australian Hazchem Code: 3[Y]

Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 1 Flammability: 3 Reactivity: 0

Label Hazard Warning:

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

Label Precautions:

Avoid breathing vapor.
Keep container closed.
Use with adequate ventilation.
Wash thoroughly after handling.
Avoid contact with eyes, skin and clothing.
Keep away from heat, sparks and flame.

Label First Aid:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Flush skin with soap or mild detergent and water for at least 15 minutes. Wash contaminated clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. In all cases call a physician.

Product Use:

Laboratory Reagent.

Revision Information:

No Changes.

Disclaimer:

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: Environmental Health & Safety

Phone Number: (314) 654-1600 (U.S.A.)