# Material Safety Data Sheet

MSDS No.1

Date of Preparation: 1/05 Revision: 2

# **Section 1 - Chemical Product and Company Identification**

Product/Chemical Name: Phytic Acid

INCI Name: Phytic Acid

CAS#: 83-86-3

Manufacturer: Biosil Technologies, Inc.

510 East 31st Street Paterson, N.J. Phone (973) 684-2000

Fax (973) 742-9048

CHEMTREC 24-HR EMERGENCY RESPONSE NUMBER: 1-800-424-9300

INTERNATIONAL CALLS: COLLECT 703-527-3887 CHEMTREC should only be called in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals.

# **Section 2 - Composition / Information on Hazardous Ingredients**

This product does not contain any active material considered hazardous as defined in 29 CFR 1910.120

#### **Section 3 - Hazards Identification**

#### **Potential Health Effects**

**HMIS** 1 F 1 R 0 PPE<sup>†</sup>

There are no potential health effects expected from handling this material. Good manufacturing practices are always recommended when handling any chemical. There are no significant laboratory data to suggest any hazard to humans. Physical/Chemical Hazards: This material is corrosive.

Carcinogenicity: IARC, NTP, and OSHA do not list this product as a carcinogen.

#### **Section 4 - First Aid Measures**

**Inhalation:** Short –term harmful health effects are not expected from vapor-generated at ambient temperatures. If first aid is required move victim to fresh air.

Eye Contact: May cause severe eye irritation. Flush immediately with water for 15 minutes. Obtain medical attention if severe irritation occurs.

Skin Contact: May cause severe irritation or discomfort. Remove contaminated clothing and wash with soap and

Ingestion: May cause abdominal discomfort, nausea, vomiting, and diarrhea. Give two glasses of water. Do not induce vomiting. Obtain medical attention.

After first aid, get appropriate in-plant, paramedic, or community medical support.

# **Section 5 - Fire-Fighting Measures**

Flash Point: > 200°C Done by Pensky - Martens closed cup

Flash Point Method: ASTM D-93 Flammability Classification: 1

**Extinguishing Media:** Use water spray, carbon dioxide, alcohol type or universal type foam

applied in accordance with the manufacturer's instructions.



**Fire-Fighting Instructions:** Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode. Section 6 -Accidental Release Measures

Safeguards (Personnel): Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean up.

**Spill /Leak Procedures:** Collect for disposal in accordance with applicable Federal, State, or local regulations. Containment: For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

### **Section 6 - Accidental Release Measures**

**Safeguards** (**Personnel**): Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean up.

Spill /Leak Procedures: Collect for disposal in accordance with applicable Federal, State, or local regulations.
Containment: For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

### **Section 7 - Handling and Storage**

Handling Precautions: (Personnel) Safety glasses and PVC gloves.

Storage Requirements: Keep container tightly closed.

# **Section 8 - Exposure Controls / Personal Protection**

**Engineering Controls:** No special engineering controls are required under normal use.

**Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

### Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear an MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

**Protective Clothing/Equipment:** Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Contaminated Equipment:** Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

#### **Section 9 - Physical and Chemical Properties**

Physical State: Liquid Water Solubility: Soluble

Appearance and Odor: Light yellow, mild

Specific Gravity (H<sub>2</sub>O=1, at 25 °C): Unknown

Boiling Point: 104°C@ 760mmHg

Freezing/Melting Point: Unknown

## **Section 10 - Stability and Reactivity**

**Stability:** Stable at room temperature in closed containers under normal storage and handling conditions. Avoid heating, as this causes hydrolysis. Avoids contact with metals as it will vigorously react. Decomposes to phosphoric acid.

Chemical Incompatibilities: None known

### **Section 11- Toxicological Information**

A knowledge of the available toxicology information and of the chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

### **Section 12 - Ecological Information**

Easily biodegradable. 48 hour LD<sub>50</sub> value on *Oryzias latipes* =210mg/L

### **Section 13 - Disposal Considerations**

**Disposal:** Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

### **Section 14 - Transport Information**

#### **DOT Transportation Data (49 CFR 172.101):**

**Shipping Name:** Corrosive

**Hazard Class:** 8

# **Section 15 - Regulatory Information**

TSCA Inventory Status: Listed

EPA Regulations: SARA 311/312 Codes: None

**State Regulations:** 

State Component CAS # Wt.

Massachusetts not regulated New Jersey not regulated Pennsylvania not regulated

### **Section 16 - Other Information**

#### Prepared By:

#### **Biosil Technologies Inc.**

Paterson, N.J. 07504

**Disclaimer:** We believe the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of the product are not within our control, it is the user's obligation to determine the conditions of safe use of this product.